

FIRESTONE DIRT TIRE SPEC SHEET

WEISEL RACING EQUIPMENT, INC.

5080 KERNSVILLE ROAD, P.O. BOX 75, OREFIELD, PA 18069

PH: 610 395-5303

www.keystonelegends.com email: klascar@ptd.net

PRICE / SPEC LIST EFFECTIVE February 15, 2012

DIRT TRACK TIRES

SIZE	COMP.	PRICE	RIM	S.W.	DIA.	TREAD	WT.	CIRC.	TUBE
6.00/12.30-15A	DH	99.00	10.0	12.6	27.3	9.8	18.6	85.7	D4519
6.00/12.30-15A	DS	99.00	10.0	12.6	27.3	9.8	18.6	85.7	D4519
*6.00/12.50-15A	DSS	99.00	10.0	12.8	26.7	10.5	18.7	84.0	D4519
*6.00/12.50-15A	DS	99.00	10.0	12.8	27.3	10.5	18.7	85.8	D4519
6.00/12.50-15A	DH	99.00	10.0	12.8	27.3	10.5	18.7	85.8	D4519
11.0/27.5-15A	17	99.00	10.0	14.4	28.0	11.3	18.5	89.0	D4519
11.0/27.5-15A	D2	99.00	10.0	14.4	28.0	11.3	18.5	89.0	D4519
*12.0/27.5-15A	17	99.00	10.0	14.8	28.0	12.3	20.5	89.0	D5025
*12.0/27.5-15A	D2	99.00	10.0	14.8	28.0	12.3	20.5	89.0	D5025
12.0/30.0-15A	D0	99.00	12.0	14.7	30.3	12.3	22.0	95.5	D5025
12.0/30.0-15A	D2	99.00	12.0	14.7	30.3	12.3	22.0	95.5	D5025
*13.0/29.0-15A	17	99.00	12.0	15.5	29.6	12.3	24.9	93.0	D5025
*13.0/29.0-15A	D0L	99.00	12.0	15.5	29.0	12.3	24.9	91.0	D5025
*13.0/29.0-15A	D1	99.00	12.0	15.5	29.6	12.3	24.9	93.0	D5025
*13.0/29.0-15A	D2	99.00	12.0	15.5	29.6	12.3	24.9	93.0	D5025
*13.0/29.0-15A	D2L	99.00	12.0	15.5	29.0	12.3	24.9	91.0	D5025
13.0/29.0-15A	B4	99.00	12.0	15.5	29.6	12.3	24.9	93.0	D5025
13.0/29.0-15A	B5	99.00	12.0	15.5	29.6	12.3	24.9	93.0	D5025
13.0/29.0-15A	B8	99.00	12.0	15.5	29.6	12.3	24.9	93.0	D5025
13.0/30.0-15A	D0	99.00	12.0	16.1	30.2	13.5	24.5	95.0	D5025
13.0/30.0-15A	D1	99.00	12.0	16.1	30.2	13.5	24.5	95.0	D5025
13.0/30.0-15A	D2	99.00	12.0	16.1	30.2	13.5	24.5	95.0	D5025
13.0/31.5-15A	17	99.00	14.0	18.0	31.5	13.2	29.0	98.0	D6028
13.0/31.5-15A	D1	99.00	14.0	18.0	31.5	13.2	29.0	98.0	D6028
13.0/31.5-15A	D2	99.00	14.0	18.0	31.5	13.2	29.0	98.0	D6028
14.0/31.5-15A	D2	99.00	14.0	18.0	31.5	13.2	29.0	98.0	D6028
14.0/31.5-15A	B5	99.00	14.0	18.0	31.5	13.2	29.0	98.0	D6028
14.0/31.5-15A	B8	99.00	14.0	18.0	31.5	13.2	29.0	98.0	D6028
16.0/32.5-15A	D1	99.00	16.0	20.1	32.3	15.3	35.5	101.5	D6028
16.0/32.5-15A	D2	99.00	16.0	20.1	32.3	15.3	35.5	101.5	D6028
16.0/32.5-15A	B5	99.00	16.0	20.1	32.3	15.3	35.5	101.5	D6028
16.0/33.0-15A	17	129.00	17.0	21.5	33.1	16.0	33.5	104.0	D6028
16.0/33.0-15A	30	129.00	17.0	21.5	33.1	16.0	33.5	104.0	D6028
16.0/33.0-15A	B4	129.00	17.0	21.5	33.1	16.0	33.5	104.0	D6028

17 compound is soft and equivalent to D0 designation

L or S designation behind compound designation means 'low' or 'short' circumference.

Soft 17-D0 D1 D2 B4 B5 B6 B8 Hard